



Point of Use Water Heaters



**HOT WATER WHERE
YOU NEED IT!**



The Everflo range of point of use water heaters includes wall mounted units, under sink units and small hand wash units. All our models are manufactured using quality materials and components to our exacting standards.

With units ranging from a simple hand wash model to units with an impressive 100 litre capacity, capable of supporting multiple outlets, the Everflo portfolio offers a comprehensive selection to meet any application.

Features and benefits

- Cheaper and easier to install than a full central water heating system
- Wide range of types and capacities to suit various applications
- Helps meet legal requirements to provide hot water for hygiene purposes
- Electric vented and unvented options available
- Minimal ongoing maintenance and servicing costs
- Quiet operation at just 15dB on each unit
- 1 Year guarantee (see back page for more information)
- Typical applications include: Office Buildings, Cafés, Washrooms, Workshops and Outbuildings

EPU-HW

Small hand wash unit, designed for easy operation. Convenient and easy to install anywhere where there is a water and a power supply.



WEIGHT (kg)	1.6	LOAD PROFILE	XXS
DEPTH (mm)	91	IP RATING	IPX4
HEIGHT (mm)	222	RATED OUTPUT	3kW
WIDTH (mm)	169	RATED VOLTAGE	230V
SPOUT LENGTH (mm)	195	INPUT PRESSURE	1 - 7 bar
ERP	A	THERMOSTAT RANGE	35 - 50°C
EFFICIENCY (%)	37	MCB / FUSE RATING	13A
AEC (kWh/y)	509		

EPU-OS5

Ideal for providing hot water to a single basin or sink, these single point units are available with a 5 litre capacity ideal for use in a small kitchen.



CAPACITY (ltr)	5	LOAD PROFILE	XXS
WEIGHT (kg)	3.4	TYPE	Vented
DEPTH (mm)	215	IP RATING	IPX4
HEIGHT (mm)	420	RATED OUTPUT	2kW
WIDTH (mm)	252	RATED VOLTAGE	230V
SPOUT LENGTH (mm)	250	CABLE LENGTH (mm)	700
ERP	A	INPUT PRESSURE (Min)	0.3 bar
EFFICIENCY (%)	37	THERMOSTAT RANGE	35 - 85°C
AEC (kWh/y)	499	MCB / FUSE RATING	13A



EPU-US10 and EPU-US15

Available in 10 or 15 litre volumes, these units fit under a basin or sink and can supply hot water to up to three hand basins or a kitchen sink.



CAPACITY (ltr)	10	15	TYPE	Unvented
WEIGHT FULL (kg)	17	22	IP RATING	IPX4
DEPTH (mm)	291	329	RATED OUTPUT	2kW
HEIGHT (mm)	347	375	RATED VOLTAGE	230V
WIDTH (mm)	340	360	CABLE LENGTH (mm)	1020
ERP	C	C	INPUT PRESSURE (Max)	6 bar
EFFICIENCY (%)	29	29	THERMOSTAT RANGE	35 - 75°C
AEC (kWh/y)	636	636	MCB / FUSE RATING	13A
LOAD PROFILE	XXS	XXS		

EPU-WM30, EPU-WM50 and EPU-WM100

Wall mounted water heaters available in 30, 50 or 100 litre volume, these high-capacity units can provide sufficient hot water to meet the needs of up to 10 hand basins or a full en-suite bathroom with a shower.



CAPACITY (ltr)	30	50	100	TYPE	Unvented
WEIGHT FULL (kg)	47	77	127	IP RATING	IPX1
DEPTH (mm)	555	555	555	RATED OUTPUT	3kW
HEIGHT (mm)	593	817	1211	RATED VOLTAGE	230V
WIDTH (mm)	478	478	478	INPUT PRESSURE (Max)	12 bar
ERP	D	D	D	THERMOSTAT RANGE	35 - 65 °C
EFFICIENCY (%)	31	35	36		
AEC (kWh/y)	593	1462	2849		
LOAD PROFILE	S	M	L		



Point of Use Water Heaters

Everflo

Unit 11 Capital Industrial Estate
Crabtree Manorway South, Belvedere
Erith, Kent DA17 6BJ

Sales Enquiries: 0208 3123720 Technical Helpline: 0330 999 0035

E-mail: sales@everflo-cylinders.co.uk

www.everflo-cylinders.co.uk

Guarantee Information

Everflo point of use water heaters are covered by a one-year warranty from the manufacturer starting on the date of purchase (three years on the inner stainless steel vessel on 30L to 100L models). In the unlikely event of a fault within the guarantee period, the customer must phone the manufacturer on **0330 999 0035** to obtain a returns reference. The product must then be returned to the retailer that sold it, making sure to quote the returns number, for an exchange.

For spare parts please call **0330 999 0035**. Note: On-site field support is not provided for these products.